


MDT 259 J12





Potain Plus

Power Control

Top Site

Top Tracing 3










Mast - Reactions


6.6 ft - P 602B									
MAJL (ft)	82	98	115	131	148	164	180	197	213
↑ (ft)	224.7	224.7	224.7	224.7	224.7	224.7	213.9	213.9	213.9
↑/P+ (ft)	224.7	224.7	224.7	224.7	224.7	224.7	213.9	213.9	213.9
	6.6 ft	1	1	1	1	1	1	1	1
	10.9 ft	2	2	2	2	2	1	1	1
	16.4 ft	12	12	12	12	12	12	12	12
F2 (USt)	● 200	196	201	198	198	198	196	196	197
	■ 329	328	334	331	338	339	307	306	313
F3 (USt)	● 147	143	146	142	141	141	138	137	138
	■ 284	282	286	282	287	289	255	254	260

6.6 ft - V 60A -									
MAJL (ft)	82	98	115	131	148	164	180	197	213
↑ (ft)	206	211.3	206	211.3	211.3	211.3	211.3	211.3	211.3
↑/P+ (ft)	206	211.3	206	211.3	211.3	211.3	211.3	211.3	211.3
	6.6 ft	1	1	1	1	1	1	1	1
	10.9 ft	2	1	2	1	1	1	1	1
	16.4 ft	10	11	10	11	11	11	11	11
F1 (USt)	● 113	114	114	115	115	115	119	119	119
	■ 145	152	147	152	156	157	155	154	158

6.6 ft - V 63A -									
MAJL (ft)	82	98	115	131	148	164	180	197	213
↑ (ft)	228	233.6	233.6	233.6	233.6	233.6	233.6	228	228
↑/P+ (ft)	228	233.6	233.6	233.6	233.6	233.6	233.6	228	228
	6.6 ft	1	1	1	1	1	1	1	1
	10.9 ft	1	0	0	0	0	0	1	1
	16.4 ft	11	12	12	12	12	12	11	11
F1 (USt)	● 133	134	136	136	136	136	140	135	135
	■ 181	188	191	189	193	193	191	182	186



6.6 ft - ZD 463 - 									
AVAIL (ft)	82	98	115	131	148	164	180	197	213
 (ft)	168	168	168	168	168	168	162.7	162.7	162.7
 / P+ (ft)	168	168	168	168	168	168	162.7	162.7	157.2
	6.6 ft	1	1	1	1	1	1	1	1
	10.9 ft	1	1	1	1	1	2	2	2
	16.4 ft	9	9	9	9	9	8	8	8
FI (USt)	● 113	111	114	112	112	113	116	116	114
	■ 130	129	133	129	134	135	125	124	129











Note: When "ASCE" is noted in this data sheet it is referring to 115 mph Wind Zone, Exposure B, Design Wind Speed = 98 mph. See back cover for design wind speed calculations.





Anchorage



Lest de base

 (USt) /  6.6 ft - V 60A - 										
 (ft)	82	98	115	131	148	164	180	197	213	
211.3		145.5		145.5	145.5	145.5	145.5	145.5	145.5	
206	145.5	145.5	145.5	132.3	145.5	145.5	132.3	132.3	132.3	
189.6	105.8	105.8	105.8	105.8	105.8	105.8	105.8	105.8	105.8	
173.2	79.4	79.4	79.4	79.4	79.4	79.4	92.6	92.6	92.6	
156.8	66.1	66.1	66.1	66.1	66.1	66.1	66.1	66.1	66.1	
140.4	52.9	52.9	52.9	52.9	52.9	52.9	52.9	52.9	52.9	
124	39.7	39.7	39.7	39.7	39.7	39.7	39.7	39.7	39.7	
107.6	39.7	39.7	39.7	39.7	26.5	26.5	26.5	26.5	26.5	
91.2	39.7	39.7	39.7	39.7	26.5	26.5	26.5	26.5	26.5	
74.8	39.7	39.7	39.7	39.7	26.5	26.5	26.5	26.5	26.5	

 (USt) /  6.6 ft - V 63A - 										
 (ft)	82	98	115	131	148	164	180	197	213	
233.6		198.4	198.4	198.4	198.4	198.4	198.4			
228	198.4	185.2	185.2	185.2	185.2	185.2	185.2	185.2	185.2	
211.6	158.7	158.7	158.7	145.5	158.7	158.7	145.5	145.5	145.5	
195.2	132.3	119.1	119.1	119.1	119.1	119.1	119.1	105.8	119.1	
178.8	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	
162.4	79.4	79.4	79.4	66.1	66.1	66.1	79.4	79.4	79.4	
146	66.1	66.1	66.1	52.9	52.9	52.9	66.1	66.1	66.1	
129.6	52.9	52.9	52.9	39.7	39.7	39.7	52.9	52.9	52.9	
113.2	39.7	39.7	39.7	39.7	26.5	26.5	39.7	39.7	26.5	
96.8	39.7	39.7	26.5	26.5	26.5	26.5	26.5	26.5	26.5	
80.4	39.7	39.7	26.5	26.5	26.5	26.5	26.5	26.5	26.5	

 (USt) /  6.6 ft - ZD 463 - 										
 (ft)	82	98	115	131	148	164	180	197	213	
168	132.3	126.8	132.3	126.8	121.3	126.8				
162.7	126.8	121.3	121.3	121.3	115.7	115.7	132.3	132.3	132.3	
146.3	104.7	99.2	104.7	99.2	93.7	93.7	110.2	110.2	110.2	
129.9	88.2	82.7	82.7	82.7	77.2	77.2	88.2	88.2	88.2	
113.5	77.2	71.7	71.7	71.7	66.1	66.1	66.1	71.7	66.1	
97.1	77.2	71.7	71.7	71.7	66.1	66.1	55.1	49.6	55.1	
80.7	77.2	71.7	71.7	71.7	66.1	66.1	55.1	44.1	55.1	
64.3	77.2	71.7	71.7	71.7	66.1	66.1	55.1	44.1	55.1	

Load curves



		(ft)	56	66	72	82	89	98	105	115	121	131	138	148	154	164	171	180	187	197	203	213	ft
		13.2 USt			6.6 USt																		
213	10 → 57	101 - 109	13.2	11.2	10	8.6	7.8	6.8	6.6	6.3	5.9	5.4	5.1	4.7	4.4	4.1	3.9	3.7	3.5	3.3	3.1	2.95	USt
	10 → 61	109 - 118	13.2	12.3	11	9.4	8.6	7.5	7	6.6	6.4	5.9	5.5	5.1	4.8	4.5	4.3	4	3.8	3.6	3.4	3.2	USt P_+
197	10 → 61	109 - 117	13.2	12.1	10.8	9.3	8.5	7.5	6.9	6.6	6.3	5.8	5.5	5.1	4.8	4.5	4.3	4	3.8	3.6			USt
	10 → 66	118 - 127	13.2	13.2	11.9	10.3	9.4	8.2	7.6	6.8	6.6	6.4	6	5.5	5.3	4.9	4.7	4.3	4.2	3.9			USt P_+
180	10 → 62	112 - 120	13.2	12.4	11.1	9.6	8.8	7.7	7.1	6.6	6.5	6	5.6	5.2	5	4.6	4.4	4.1					USt
	10 → 68	121 - 130	13.2	13.2	12.3	10.6	9.6	8.5	7.9	7	6.6	6.5	6.2	5.7	5.4	5	4.8	4.5					USt P_+
164	10 → 62	112 - 120	13.2	12.5	11.2	9.6	8.8	7.7	7.2	6.6	6.6	6	5.7	5.2	5	4.6							USt
	10 → 68	121 - 131	13.2	13.2	12.3	10.6	9.7	8.5	7.9	7.1	6.6	6.6	6.2	5.7	5.4	5							USt P_+
148	10 → 64	114 - 123	13.2	12.8	11.4	9.9	9	7.9	7.3	6.6	6.6	6.1	5.8	5.4									USt
	10 → 69	124 - 133	13.2	13.2	12.5	10.9	9.9	8.7	8.1	7.3	6.8	6.6	6.4	5.9									USt P_+
131	10 → 66	118 - 128	13.2	13.2	11.9	10.3	9.4	8.3	7.7	6.9	6.6	6.4											USt
	10 → 71	128 - 131	13.2	13.2	13.1	11.3	10.3	9.1	8.4	7.6	7.1	6.6											USt P_+
115	10 → 64		13.2	12.9	11.5	9.9	9.1	8	7.4	6.6													USt
	10 → 69		13.2	13.2	12.7	10.9	10	8.8	8.2	7.3													USt P_+
98	10 → 65		13.2	13.1	11.8	10.1	9.3	8.2															USt
	10 → 71		13.2	13.2	12.9	11.2	10.2	9															USt P_+
82	10 → 65		13.2	13.2	11.8	10.2																	USt
	10 → 71		13.2	13.2	13	11.2																	USt P_+

$$W_{L1} = W_{L2} - 0.63 \text{ USt max.}$$



		(ft)	56	66	72	82	89	98	105	115	121	131	138	148	154	164	171	180	187	197	203	213	ft
		13.2 USt			6.6 USt																		
213	8 → 57	102 - 105	13.2	11.2	10	8.6	7.9	6.9	6.6	5.9	5.5	5	4.7	4.3	4.1	3.7	3.5	3.3	3.1	2.9	2.75	2.6	USt
	8 → 62	110 - 113	13.2	12.4	11.1	9.5	8.7	7.6	7	6.3	6	5.5	5.2	4.7	4.5	4.1	3.9	3.6	3.4	3.2	3.1	2.85	USt P_+
197	8 → 61	110 - 112	13.2	12.2	10.9	9.4	8.6	7.6	7	6.4	6	5.5	5.2	4.7	4.5	4.1	3.9	3.7	3.5	3.3			USt
	8 → 66	119 - 121	13.2	13.2	12	10.3	9.4	8.3	7.7	6.9	6.4	6	5.7	5.2	4.9	4.6	4.3	4	3.8	3.6			USt P_+
180	8 → 62	113 - 115	13.2	12.5	11.2	9.7	8.8	7.8	7.2	6.6	6.2	5.6	5.3	4.9	4.6	4.3	4.1	3.8					USt
	8 → 68	122 - 124	13.2	13.2	12.3	10.6	9.7	8.6	7.9	7.1	6.6	6.2	5.8	5.4	5.1	4.7	4.5	4.2					USt P_+
164	8 → 63	113 - 115	13.2	12.5	11.2	9.7	8.9	7.8	7.2	6.6	6.2	5.7	5.3	4.9	4.6	4.3							USt
	8 → 68	122 - 125	13.2	13.2	12.4	10.7	9.7	8.6	8	7.1	6.7	6.2	5.9	5.4	5.1	4.7							USt P_+
148	8 → 64	115 - 118	13.2	12.8	11.5	9.9	9.1	8	7.4	6.7	6.4	5.8	5.5	5									USt
	8 → 69	125 - 127	13.2	13.2	12.6	10.9	10	8.8	8.2	7.3	6.8	6.3	6	5.5									USt P_+
131	8 → 66	119 - 122	13.2	13.2	12	10.3	9.4	8.3	7.7	6.9	6.6	6.1											USt
	8 → 72	129 - 131	13.2	13.2	13.1	11.4	10.4	9.2	8.5	7.6	7.1	6.6											USt P_+
115	8 → 64		13.2	12.9	11.6	10	9.1	8.1	7.5	6.7													USt
	8 → 70		13.2	13.2	12.7	11	10.1	8.9	8.2	7.4													USt P_+
98	8 → 66		13.2	13.2	11.8	10.2	9.3	8.2															USt
	8 → 71		13.2	13.2	13	11.2	10.3	9.1															USt P_+
82	8 → 66		13.2	13.2	11.9	10.3																	USt
	8 → 71		13.2	13.2	13.1	11.3																	USt P_+














$$W_{L1} = W_{L2} - 0.18 \text{ USt max.}$$












Jib weight & counter-jib ballast

	(lb) (+/- 5%)									CBS - 10,141 lb	CBU - 6,768 lb	CBY - 3,373 lb
				10,141 lb	3,373 lb	(lb)	6,768 lb	3,373 lb	(lb)			
213 ft	27,448	26,764	27,613	5	1	54,079	7	2	54,123			
197 ft	26,830	26,169	26,963	5	1	54,079	7	2	54,123			
180 ft	26,147	25,485	26,279	5	0	50,706	7	1	50,750			
164 ft	24,052	23,391	24,185	4	1	43,938	6	1	43,982			
148 ft	24,339	23,678	24,471	4	1	43,938	6	1	43,982			
131 ft	22,245	21,583	22,377	4	0	40,565	6	0	40,609			
115 ft	21,914	21,253	22,046	3	2	37,170	5	1	37,214			
98 ft	20,084	19,423	20,216	3	1	33,797	5	0	33,841			
82 ft	19,004	18,342	19,136	3	0	30,424	4	1	30,446			

Dimensions and weight

Slewing crane part :  213 ft -  -  50 LVF

Slewing crane part		L (ft)	W (ft)	H (ft)	lb (+/- 5%)
Counter-jib		36.1 36.1	3.8 3.8	8.1 8.1	19,213 18,629
Towerhead + cab		16.1	7.5	8.3	18,618
Hoisting winch (+ rope)		10.6 10.6	8.1 10.8	6.2 5.8	6,945 9,235
Jib section		35.5	5.6	8.9	7,760
Jib section		33.8 33.5 33.6 33.4	3.9 3.9 3.9 3.9	7.9 7.8 6.9 6	5,335 3,439 2,723 1,753
Jib section		17.3 16.7	3.9 3.9	7.8 5	2,116 683
Jib section		16.7	3.9	4.6	485
Trolley		6.1	5	3.4	882
Pulley block		3.9	1.4	7.6	1,003
Trolley		5.2	5	3.2	463
Trolley		5.6	5	3.4	540
Pulley block		5.4	0.7	5.8	992
		3.6	0.9	5.3	584


Crane tower			L (ft)	W (ft)	H (ft)	lb (+/- 5%)
Telescopic cage T 61		□ 6.6 ft	35.5	13.6	14.7	21,385
K60/K60		□ 6.6 ft	7.3	8.1	8.2	4,365
K 649B KM 649E		□ 6.6 ft	33.6 33.8	6.8 6.7	6.7 6.7	11,663 10,692
K 649A KMT 649A KR 649A KRMT 649A		□ 6.6 ft	17.2 17.2 17.2 17.2	6.8 6.8 6.9 6.9	6.7 6.7 6.8 6.8	6,184 5,666 7,165 6,724
K 649C KRMT 649C		□ 6.6 ft	11.7 11.7	6.8 6.9	6.7 6.8	4,376 5,401
Fixing angles		P 602B	2.1	2.1	4.2	650
Basic mast unit		V 60A V 63A	16.4 32.9	7.9 7.9	7.9 7.9	9,674 16,502
Struts		V 60A V 63A	14.8 14.8	1 1.1	1 1.1	919 1,135
Half-bearer		V 60A V 63A	22 22	2.3 2.3	7.6 7.6	3,519 4,079
Cross girder		ZD 463	25.1	3.8	4.5	7,904
1/2 Cross girder		ZD 463	11.2	2.3	4.4	3,649

Mechanisms

480 V - 60 Hz											hp	kW		
	50 LVF 30 Optima	fpm	105	135	185	267	54	71	97	135	50	37	1,106 ft	
		USt	6.6	5	3.3	1.1	13.2	9.9	6.6	2.5				
	90 HPL™ 30	fpm	174	226	320	541	722	90	118	171	305	361	90	66
USt		6.6	5	3.3	1.7	0.8	13.2	9.9	6.6	3.3	2.5			
	6 DVF 4 Optima	fpm	0 → 164 (13.2 USt) 0 → 328 (6.6 USt) 0 → 394 (3.3 USt)								5.5	4		
	RVF 162 Optima+	rpm	0 → 0.9								2 x 7.5	2 x 5.5		

480 V (+6% -10%) 60 Hz	50 LVF: 58 → 38 kVA 90 HPL™: 90 → 54 kVA		

50 LVF 30 Optima



These mast combinations meet the EN 14439 and ASME B30.3-2012 specifications for "out of service" wind conditions, provided the illustrated wind speed matches required design wind for the location of the tower crane. The "out of service" design wind speed was determined in accordance with ASCE 7-10, Figure 26.5-A. The wind velocity, used for this configuration was 98 mph (158 kph), which represents a nominal design 3-second wind gust at 33 ft (10 m) above ground for Exposure B category A. Factor of 0.85 was applied to the 50-year ultimate design wind speed of 115 mph (185 kph), per ASCE 37-02, with the assumption that this crane is considered a temporary structure used during a construction period of 2 years or less.

	Jib elevation		Total ballast weight		Travelling
	Standard equipment		Jib weight		Required power
	Options		Lorry 44 ft		Power Control Function: winch speeds adapted to the available power
	Potain Plus function: Plus load curves		Container High Cube 40 ft, and/or Flat Rack 20 ft		Consult us
	Hook heights with Plus load curves		Hoisting		
	Reactions in service		Trolleying		
	Reactions out of service		Slewing		



This commercial document is not legally binding. For any technical information, please refer to the corresponding instructions.

